

VD-C3200S

2 MP Network Dome Camera



Model	VD-C3200S
Image Sensor	1/3" CMOS
Signal system	PAL/NTSC
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.05Lux@ (F1.2 , AGC ON)
Shutter Time	automatic
Lens	2.7-9mm@F1.2 angle of view : 101°-30°
Lens Mount	φ 14
Auto Iris Lens	Dcdrive
Angle adjustment	Horizontal : 0°~360° , vertical : 0°~75° , rotating : 0°~360°
Day& Night	Electronic color to black
Compression Standard	
Video Compression	H.264/MPEG4
Bit Rate	32 Kbps~8Mbps
Audio Compression	OggVorbis
Image	
Max Image Resolution	1920×1080
Frame Rate	50Hz:25fps (1280×960) , 25fps (1280×720) 60Hz:30fps (1280×960) , 30fps (1280×720)
Network	
Storage	Support SD/SDHC
Alarm Trigger	Motion detection
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE (FTP,SMTP,NTP,SNMP)
Common functions	flicker, dual stream, heartbeat,
Interface	
Audio Input	1 channel 3.5mm audio interface (2.0~2.4Vp-p, 1k Ohm)
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	1 channel
Alarm Output	1 channel
Video output	1.0Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%
Power Consumption	4W MAX
Dimensions	φ 145×132.8
Weight	900g

Features

- 2 megapixel (1920 x 1080)
- High Resolution
- 1/3" Progressive Scan CCD
- Support SD/SDHC card storage
- PTZ