

# VD-C3200WDT

# 2 MP WDR Vandal-Proof Network Dome Camera



Model	VD-C3200WDT
Image Sensor	1/3" CCD
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.001Lux@ ( F1.2 , AGC ON)
Shutter Time	1/25s~1/100,000s
Lens	2.7-9mm@F1.2 angle of view : 101°-30.4°
Lens Mount	φ14
Auto Iris Lens	DC drive
Angle adjustment	Horizontal : 0°~360° , vertical : 0°~75° , rotating : 0°~360°
Day& Night	ICR Cut Filter
Compression Standard	
Video Compression	H.264/MJPEG
Bit Rate	32 Kbps~16Mbps
Audio Compression	G.711
Image	
Max Image Resolution	1920×1080
Frame Rate	50Hz:25fps ( 1280×960 ) , 25fps ( 1280×720 ) 60Hz:30fps ( 1280×960 ) , 30fps ( 1280×720 )
Network	
Storage	Support SD/SDHC,NAS/ISCS
Alarm Trigger	Motion detection,Video loss , network disconnect, IP address conflict, storage full, storage error
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (SNMP,HTTPS,FTP,SIP,SRTP,802.1×IPV6 )
Common functions	One key reset, flicker, dual stream, heartbeat, three axis control
Interface	
Audio Input	1 channel microphone input, 3.5mm mini-jack
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	2 channel
Alarm Output	2 channel
Video output	1Vp-p Composite Output(75Ω/RCA)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE/AC24V,
Power Consumption	7.5W MAX
Impact Protection	IEC60068-275Eh, 50J; EN50102, exceeding IK10
Dimensions	φ140×114
Weight	1400g

## Features

- 2 MP (1920 x 1080) High Resolution
- 1/3" Progressive Scan CCD
- ICR Cut Filter Auto switch
- True day / night
- Support SD/SDHC card storage
- POE network functions
- IEC 60668-2-75,Eh,50j;EN50102, IK10