

VD-C3300HT

3MP Vandal-Proof Network Dome Camera



| | |
|---------------------------------|--|
| Model | VD-C3300HT |
| Image Sensor | 1/3" CCD |
| Minimum Illumination | Color : 0.1lux@(F1.2,AGC ON);B/W : 0.01Lux@ (F1.2 , AGC ON) |
| Shutter Time | 1/25s~1/100,000s |
| Lens | 4.5-10mm@F1.2 angle of view : 71.5°-33.5° |
| Lens Mount | CS Interface |
| Auto Iris Lens | DC drive |
| Angle adjustment | Horizontal : 0°~360° , vertical : 0°~75° , rotating : 0°~360° |
| Day& Night | ICR Cut Filter |
| Compression Standard | |
| Video Compression | H.264/MJPEG |
| Bit Rate | 32 Kbps~16Mbps |
| Audio Compression | G.711 |
| Image | |
| Max Image Resolution | 2048×1536 |
| Frame Rate | 50Hz:25fps (2048×1536) , 25fps (1920×1080) 25fps (1600×1200) 60Hz:30fps (2048×1536) , 30fps (1920×1080) 30fps(1600×1200) |
| Network | |
| Storage | Support SD/SDHC,NAS/ISCS |
| Alarm Trigger | Motion detection, Video loss , network disconnect, IP address conflict, storage full, storage error |
| Protocols | TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (SNMP,HTTPS,FTP,SIP,SRTP,802.1×IPV6) |
| Common functions | One key reset, flicker, dual stream, heartbeat, three axis control |
| Interface | |
| Audio Input | 1 channel microphone input, 3.5mm mini-jack |
| Audio Output | 1 channel 3.5mm audio interface (line level, 600 Ohm) |
| Communication Interface | 1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface |
| Alarm Input | 2 channel |
| Alarm Output | 2 channel |
| Video output | 1Vp-p Composite Output(75Ω/RCA) |
| General | |
| Working TemperatureAnd humidity | -10°C~60°C , humidity 90% or less (non-condensing) |
| Power Supply | DC12V±10%/POE/AC24V |
| Power Consumption | 7.5W MAX |
| Impact Protection | IEC60068-275Eh, 50J; EN50102, exceeding IK10 |
| Dimensions | φ140×114 |
| Weight | 1400g |

Features

- 3 megapixel (2048×1536) High Resolution
- Full HD 1080P real-time video
- 1/3" Progressive Scan CCD
- Support SD/SDHC card storage
- ICR Cut Filter Auto switch
- True day / night
- POE network functions
- IEC 60668-2-75,Eh,50j;EN 50102, IK10