

VD-C3500HT

5MP Vandal-Proof Network Dome Camera



Model	VD-C3500HT
Image Sensor	1/3" CCD
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.01Lux@ (F1.2 , AGC ON)
Shutter Time	1/25s~1/100,000s
Lens	4.5-10mm@F1.6 angle of view : 71.5°-33.5° 3.5*-9mm@F1.6 angle of view : 92°-36°
Lens Mount	φ17.5
Auto Iris Lens	DC drive
Angle adjustment	Horizontal : 0°~360° , vertical : 0°~75° , rotating : 0°~360°
Day& Night	ICR Cut Filter
Compression Standard	
Video Compression	H.264/MPEG4/MJPEG
Bit Rate	32 Kbps~16Mbps
Audio Compression	G.711
Audio Bit rate	64kbps
Image	
Max Image Resolution	2560×1920
Frame Rate	50Hz:6.25fps (2560×1920) 12.5fps (2048×1536) 25fps (1920×1080) , 25fps (1600×1200) , 25fps (1280×720) 60Hz : 7.5fps (2560×1920) 15fps (2048×1536) 30fps (1920×1080) ,30fps (1600×1200) ,30fps (1280×720)
Network	
Storage	Support SD/SDHC,NAS/ISCS
Alarm Trigger	Motion detection, tampering alarm , network disconnect, IP address conflict, storage full, storage error
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (SNMP,HTTPS,FTP,SIP,SRTP,802.1×IPV6)
Interface Protocols	ONVIF,PSIA,CGI
Common functions	One key reset, flicker, dual stream, heartbeat, three axis control
Interface	
Audio Input	1 channel microphone input, 3.5mm mini-jack
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	2 channel
Alarm Output	2 channel
Video output	1Vp-p Composite Output(75Ω/RCA)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE(802.3af)
Power Consumption	5.5W MAX
Impact Protection	IEC60068-275Eh, 50J; EN50102, exceeding IK10
Dimensions	φ140×114
Weight	1400g

Features

- 5 megapixel (2560×1920) High Resolution
- Full HD 1080P real-time video
- 1/3" Progressive Scan CCD
- Micro 32G SD/SDHC memory
- POE network functions
- IEC 60668-2-75,Eh,50j:EN 50102, IK10

