

# VD-C3054WDS

# 4CIF WDR Vandal-Proof Network Dome Camera



Model	VD-C3054WDS
Image Sensor	1/3" CMOS
Signal system	PAL/NTSC
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.01Lux@ ( F1.2 , AGC ON)
Shutter Time	1/50(1/60)s~1/100,000s
Lens	3.5-9mm@F1.2 angle of view : 80°-30°
Auto Iris Lens	DC drive
Angle adjustment	Horizontal : 0°~360° , vertical : 0°~75° , rotating : 0°~360°
Day& Night	Electronic color to black
Wide dynamic range	160 times
Compression Standard	
Video Compression	H.264/MJPEG
Bit Rate	32 Kbps~8Mbps
Audio Compression	OggVorbis
Image	
Max Image Resolution	PAL:704×576 ; NTSC:704×480
Frame Rate	50Hz:25fps ( 704×576 ) , 60Hz : 30fps ( 704×480 )
Network	
Storage	Support SD/SDHC,NAS/ISCS
Alarm Trigger	Motion detection, Video loss , network disconnect, IP address conflict, storage full, storage error
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE (FTP,SMTP,NTP,SNMP )
Common functions	One key reset, flicker, dual stream, heartbeat, three axis control
Interface	
Audio Input	1 channel microphone input, 3.5mm mini-jack
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	2 channel
Alarm Output	2 channel
Video output	1Vp-p Composite Output(75Ω/RCA)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE/AC24V±10%
Power Consumption	7.5W MAX
Impact Protection	IEC 60068-2-75 测试 , Eh, 50J:EN 50102 , 超过 IK10
Dimensions	φ140×114
Weight	1400g

## Features

- 4CIF real-time video
- 160dB wide dynamic range
- Support SD/SDHC card storage
- POE network functions
- IEC 60668-2-75,Eh,50j:EN 50102, IK10
- H.264/MJPEG Video Compression