



Model	VD-C2200S
Image Sensor	1/3" CMOS
Minimum Illumination	Color : 0.5lux@(F1.2,AGC ON);0.1lux@(F1.2,AGC ON , iso×5) B/W : 0.05Lux@ (F1.2 , AGC ON);0.01lux@ (F1.2 , AGC ON , iso×5)
Shutter Time	1/25s~1/100,000s
Lens Mount	C/CS Interface
Auto Iris Lens	DC drive
Day& Night	Electronic color to black
Compression Standard	
Video Compression	H.264/MJPEG
Bit Rate	32 Kbps~16Mbps
Audio Compression	G.711
Image	
Max Image Resolution	1600×1200
Frame Rate	50Hz:12.5fps (1600×1200) , 12.5fps (1600×712) 25fps (1280×960) 25fps (1280×720) 60Hz:15fps (1600×1200) , 15fps (1600×912) 25fps (1280×960) , 30fps (1280×720)
Network	
Storage	Support SD/SDHC,NAS/ISCS
Alarm Trigger	Motion detection,Video loss , , network disconnect, IP address conflict,storage full, storage error
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (SNMP,HTTPS,FTP,SIP,SRTP,802.1×IPV6)
Common functions	e-PTZ , One key reset, flicker, dual stream, heartbeat,
Interface	
Audio Input	1 channel microphone input, 3.5mm mini-jack
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	1 channel
Alarm Output	1 channel
Video output	1Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE/AC24V
Power Consumption	9.5W MAX
Dimensions	68×57×144.8
Weight	550g

Features

- 2 megapixel (1600×1200) High Resolution
- 1/3" Progressive Scan CCD
- Support SD/SDHC card storage
- ICR Cut Filter Auto switch
- True day / night
- PoE