



Model	VD-C2054HS
Image Sensor	1/3" CMOS
Signal system	PAL/NTSC
Minimum Illumination	Color : 0.02lux@(F1.2,AGC ON);B/W : 0.002Lux@ ( F1.2 , AGC ON)
Shutter Time	1/25(1/30)s~1/100,000s
Lens Mount	C/CS interface
Auto Iris Lens	DC drive
Day& Night	ICR Cut Filter
Compression Standard	
Video Compression	H.264/MJPEG
Bit Rate	32 Kbps~8Mbps
Audio Compression	G.711
Image	
Max Image Resolution	PAL:704×576 NTSC:704×480
Frame Rate	50Hz:25fps ( 704×576 ) 60Hz:30fps ( 704×480 )
Network	
Storage	Support SD/SDHC,NAS/ISCS
Alarm Trigger	Motion detection, Video loss , network disconnect, IP address conflict,storage full, storage erro
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (SNMP,HTTPS,FTP,SIP,SRTP,802.1×IPV6 )
Common functions	One key reset, flicker, dual stream, heartbeat,
Interface	
Audio Input	1 channel microphone input, 3.5mm mini-jack
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	1 channel
Alarm Output	1 channel
Video output	1Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	AC24V±10%/DC12V±10%/POE
Power Consumption	10.5W MAX
Dimensions	67.95×56×114.8
Weight	800g

### Features

- 4CIF real-time video
- H.264/MJPEG Video Compression
- Support SD/SDHC card storage
- ICR Cut Filter Auto switch
- True day / night
- PoE