



Model	VR-8012T
Video/Audio Input	
Analog Video Input:	12 channel BNC (1.0 Vp-p, 75 Ω), PAL /NTSC Self-adaptive,
Network video Input:	12 channel SD/6 channels HD 720P/3 channel UXGA Network video
Composited Video Input:	20 channel (Analog + Network)
Audio Input :	12 channel BNC (2.0 Vp-p, 1k Ω)
Video/Audio Output	
CVBS Output	2 channel, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
HDMI Output	1 channel, resolution: 1024 × 768/ 60 Hz ,1280 × 1024/ 60 Hz, 1920 × 1080/ 60 Hz
VGA Output	1 channel, resolution: 1024 × 768/ 60 Hz ,1280 × 768/ 60 Hz, 1280 × 1024/ 60 Hz
Audio Output	2 channel, BNC (600Ω)
Audio/Video coding	
Video Compression	H.264
Video decoding resolution	4CIF/DCIF/2CIF/CIF/QCIF
Video frame rate	PAL:1/16--25fps,NTSC:1/16--30fps
video bit rate	32Kbps-2048Kbps,max 6411Kbps
Audio Compression:	OggVorbis
Audio bit rat	16Kbps
Stream type	Composite/Video
Dual stream	Yes
Playback resolution:	UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback:	12 channel
Hard disk	
SATA:	8 SATA interfaces
Capacity:	Up to 2TB capacity for each disk
External Interface	
voice Input:	2, BNC (2.0Vp-p, 1kΩ)
Network Interface:	1,, RJ45 10M / 100M / 1000M Ethernet interface
Serial Interface:	1,RS-485, 1 RS-232 , 1 RS-485 for keyboard
USB Interface:	3,USB 2.0
Alarm Input:	16 channel
Alarm Output:	4 channel
General	
Power Supply:	AC220V,47--63HZ
Power Consumption	≤70W
Working Temperature:	-10°C--+55°C
Working Humidity:	10%--90%
Chassis:	19-inch rack-mounted 2U chassis
Dimensions	445mm×470mm×90mm
Weight(Without HDD):	≤ 8kg

Features

- Support 8 SATA Interfac
- Support 16 channel synchronous playback
- HDMI output at up to 1920×1080P resolution
- VGA output at up to 1280×1024P resolution
- Supported Third-party (AXIS、Bosch、Panasonic、SANYO、SONY) network camera
- Supported Redundant video
- H.264 video compression