



Model	VR-9008T
Video/Audio Input	
Network video Input:	8 channel
Video/Audio Output	
CVBS Output	1 channel, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
HDMI Output	1 channel, resolution: 1024 × 768/ 60 Hz ,1280 × 720/ 60 Hz, 1280 × 1024/ 60 Hz , 1600×1200/60Hz , 1920×1080p/50Hz 1920×1080p/60Hz
VGA Output	1 channel, resolution: 1024 × 768/ 60 Hz ,1280 × 720/ 60 Hz, 1280 × 1024/ 60 Hz , 1600×1200/60Hz , 1920×1080p/60Hz
Audio Output	2 channel, BNC (600Ω)
Audio/Video coding	
Playback resolution:	5MP/3MP/1080p/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback:	8 channel
Hard disk	
SATA:	8 SATA interfaces,1 eSATA interfaces
Capacity:	Up to 4TB capacity for each disk
External Interface	
voice Input:	1, BNC (2.0Vp-p, 1kΩ)
Network Interface:	2,, RJ45 10M / 100M / 1000M Ethernet interface
Serial Interface:	1,RS-485, 1 RS-232 , 1 RS-485 for keyboard
USB Interface:	2,USB 2.0
Alarm Input:	16 channel
Alarm Output:	4 channel
General	
Power Supply:	AC220V,47--63HZ
Power Consumption	≤35W(Without HDD)
Working Temperature:	-10°C--+55°C
Working Humidity:	10%--90%
Chassis:	19-inch rack-mounted 2U chassis
Dimensions	445mm×470mm×90mm
Weight(Without HDD):	≤ 8kg

Features

- Supported Third-party (AXIS、Panasonic、SANYO、SONY) network camera
- HDMI and VGA output at up to 1920×1080P resolution
- Supported Redundant video
- ONVIF and PSIA compliant
- Support 16 channel 4CIF synchronous realtime playback
- Support IPv6
- HDMI/VGA/CVBS simultaneous video output
- Support HDD quota and group management