



Model	VD-5801
Output:	
VGA Output:	1 channel
VGA output resolution	1920×1080@60/50HZ,1600×1200@60HZ,1280×1024@60HZ , 1280×720@50/60HZ , 1024×768@60/HZ
HDMI Output:	1 channel
HDMI output resolution:	1920×1080@60/50HZ,1600×1200@60HZ,1280×1024@60HZ , 1280×720@50/60HZ , 1024×768@60/HZ
BNC output:	1 channel
Decode	
Decode resolution:	The resolution of the 500W and below
Decodes the channel:	4 channel
Decoding ability :	1 channel 500W/channel1080P/2 channel 720P/4 channel 4CIF
Image splitter :	1/4
External Interface	
Network Interface :	1, RJ45 10M / 100M / 1000M Ethernet interface
Voice intercom:	1 channel Input , 1 channel Output , 3.5mm Audio Interface (2.0Vp-p , 1KΩ)
Audio Output :	1 channel , 1 RCA Interface
Alarm Input:	4 channel
Alarm Output:	4 channel
Serial Interface:	1 RJ232 Interface,1 RJ485 Interface
General	
Power Supply:	Internal
Consumption:	≤ 15W
Working Temperature:	-10°C-- +55°C
Working Humidity:	10%--90%
Dimension:	220mm×148mm×45mm
Weight :	≤ 1.12kg

Features

- HDMI and VGA output at up to 1920×1080 resolution
- Support 1channel 1080P/2 channel 720p/4 channel 4CIF
- Support HDMI and VGA Output interface
- Support Active decoder and Passive decoder
- Support splicing video wall display