

VD-C3130HT 1.3 MP Water-Proof and Vandal-Proof Network Dome Camera



Model	VD-C3130HT
Image Sensor	1/3" CCD
Signal system	PAL
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.01Lux@ (F1.2 , AGC ON)
Shutter Time	1/4s~1/100,000s
Lens	2.8-12mm@F1.4angle of view : 89°-24°
Lens Mount	φ14
Auto Iris Lens	Dcdrive
Angle adjustment	Horizontal : 0°~360° , vertical : 0°~75° , rotating : 0°~360°
Day& Night	ICR Cut Filter
Compression Standard	
Video Compression	H.264/MJPEG
Bit Rate	32 Kbps~8Mbps
Audio Compression	OggVorbis
Image	
Max Image Resolution	1280×960
Frame Rate	50Hz:12.5fps (1280×960) , 25fps (1280×720) 60Hz:15fps (1280×960) , 24fps (1280×720)
Network	
Storage	Support SD/SDHC
Alarm Trigger	Motion detection
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE (FTP,SMTP,NTP,SNMP)
Common functions	dual stream, heartbeat
Interface	
Audio Input	1 channel 3.5mm audio interface (2.0~2.4Vp-p, 1k Ohm)
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	1 channel
Alarm Output	1 channel
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	AC24V±10%/DC12V±10%/POE (-H:AC24V±10%)
Power Consumption	9.5W MAX
Impact Protection	IEC60068-275EH, 50J; EN50102, exceeding IK10
Protection grade	IP66
Dimensions	φ150.6×123.5
Weight	1600g

Features

- 1/3" 1.3Megapixel progressive scan Aptina CCD
- Support SD/SDHC card storage
- ICR Cut Filter Auto switch
- POE
- IP66 Ingress Protection