

VD-C3200HS 2MP Water-Proof and Vandal-Proof Network Dome Camera



Model	VD-C3200HS
Image Sensor	1/3" CMOS
Signal system	PAL
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.01Lux@ (F1.2 , AGC ON)
Shutter Time	automatic
Lens	2.7-9mm@F1.2 angle of view : 101°-30.4°
Lens Mount	φ14
Auto Iris Lens	Dcdrive
Angle adjustment	Horizontal : 0°~360° , vertical : 0°~75° , rotating : 0°~360°
Day& Night	IR Cut Filter
Compression Standard	
Video Compression	H.264/MPEG4
Bit Rate	32 Kbps~8Mbps
Audio Compression	OggVorbis
Image	
Max Image Resolution	1920×1080
Frame Rate	50Hz:25fps (1280×1080) , 25fps (1280×960) 60Hz:30fps (1280×1080) , 30fps (1280×960)
Image Settings	Saturation, brightness, contrast adjustable through client software or web browser
Network	
Storage	Support SD/SDHC
Alarm Trigger	Motion detection
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE (FTP,SMTP,NTP,SNMP)
Common functions	flicker, dual stream, heartbeat,
Interface	
Audio Input	1 channel 3.5mm audio interface (2.0~2.4Vp-p, 1k Ohm)
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	1 channel
Alarm Output	1 channel
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	AC24V±10%/DC12V±10%/POE (-H:AC24V±10%)
Power Consumption	4W MAX
Impact Protection	IEC 60068-2-75 测试, Eh, 50J:EN 50102, 超过 IK10
Protection grade	IP66
Dimensions	φ150.6×123.5
Weight	1600g

Features

- 1/3" 2Megapixel progressive scan Aptina CCD
- Support SD/SDHC card storage
- ICR Cut Filter Auto switch
- PTZ
- IP66 Ingress Protection