

VD-C7200S

2 MP Vandal-Proof Network IR Dome Camera



Features

- 2 megapixel (1920 x 1080) High Resolution
- Full HD 1080P real-time video
- 1/3" Progressive Scan CCD
- Support SD/SDHC card storage
- POE network functions
- H.264/MPEG/MJPEG
- IP66 Ingress Protection
- IEC 60668-2-75, Eh, 50j; EN 50102, IK10

Model	VD-C7200S
Image Sensor	1/3" CMOS
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.001Lux@ (F1.2 , AGC ON)
Shutter Time	1/25s~1/100,000s
Lens	2.7-9mm@F1.2 angle of view : 101°-30.4°
Lens Mount	φ14
Auto Iris Lens	DC drive
Angle adjustment	Horizontal : 0°~360° , vertical : 0°~75° , rotating : 0°~360°
Day& Night	ICR Cut Filter
Compression Standard	
Video Compression	H.264/MPEG4/MJPEG
Bit Rate	32 Kbps~16Mbps
Audio Compression	G.711
Image	
Max Image Resolution	1920×1080
Frame Rate	50Hz:25fps (1280×1080) , 25fps (1280×960) 60Hz:30fps (1280×1080) , 30fps (1280×960)
Network	
Storage	Support SD/SDHC,NAS/ISCS
Alarm Trigger	Motion detection, network disconnect, IP address conflict, storage full, storage error
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (SNMP,HTTPS,FTP,SIP,SRTP,802.1×IPV6)
Common functions	One key reset, flicker, dual stream, heartbeat, three axis control
Interface	
Audio Input	1 channel microphone input, 3.5mm mini-jack
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	2 channel
Alarm Output	2 channel
Video output	1Vp-p Composite Output(75Ω/RCA)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE
Power Consumption	7.5W MAX
Impact Protection	IEC60068-275Eh, 50J; EN50102, exceeding IK10
Dimensions	φ140×114
Weight	1400g