

VD-C3054S

4CIF Network Dome Camera



Model	VD-C3054S
Image Sensor	1/4" CMOS
Minimum Illumination	Color : 0.2lux@(F1.2,AGC ON);B/W : 0.03Lux@ (F1.2 , AGC ON)
Lens	4-9mm@F1.6 angle of view : 56°-22.8°
Lens Mount	M12
Angle adjustment	Horizontal : 0°~360° , vertical : 0°~75° , rotating : 0°~360°
Day& Night	Electronic color to black
Compression Standard	
Video Compression	H.264/MPEG4
Bit Rate	32 Kbps~8Mbps
Audio Compression	OggVorbis
Image	
Max Image Resolution	704×576
Frame Rate	25fps (704×576)
Network	
Storage	Support SD/SDHC
Alarm Trigger	Motion detection
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (FTP,SMTP,NTP,SNMP)
Common functions	dual stream, heartbeat
Interface	
Audio Input	1 channel 3.5mm audio interface (2.0~2.4Vp-p, 1k Ohm)
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	2 channel
Alarm Output	2 channel
Video output	1Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%
Power Consumption	3W MAX
Dimensions	φ140×132.8
Weight	900g

Features

- H.264/ MPEG4 Video Compression
- Support SD/SDHC card storage
- POE network functions
- PTZ