

# VD-C3054HT

# 4CIF Network Dome Camera



Model	VD-C3054HT
Image Sensor	1/3" CCD
Signal system	PAL/NTSC
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.01Lux@ ( F1.2 , AGC ON)
Shutter Time	1/50(1/60)s~1/100,000s
Lens	3.5-9mm@F1.2 angle of view : 80°-30°
Lens Mount	φ14
Angle adjustment	Horizontal : 0°~360° , vertical : 0°~75° , rotating : 0°~360°
Day& Night	IR Cut Filter
Horizontal resolution	540 TVL
Compression Standard	
Video Compression	H.264/MPEG4
Bit Rate	32 Kbps~8Mbps
Audio Compression	OggVorbis
Image	
Max Image Resolution	PAL:704×576;NTSC:704×480
Frame Rate	50Hz:25fps ( 704×576 ) , 60Hz : 25fps ( 704×480 )
Network	
Storage	Support SD/SDHC
Alarm Trigger	Motion detection
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE (FTP,SMTP,NTP,SNMP )
Common functions	dual stream, heartbeat,
Interface	
Audio Input	1 channel 3.5mm audio interface (2.0~2.4Vp-p, 1k Ohm)
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	1 channel
Alarm Output	1 channel
Video output	1Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%
Power Consumption	4W MAX
Dimensions	φ140×129
Weight	1000g

## Features

- H.264/ MPEG4 Video Compression
- Support SD/SDHC card storage
- POE network functions
- PTZ