

VD-C7054HS

4CIF Network IR Dome Camera



Model	VD-C7054HS
Image Sensor	1/3" CMOS
Signal system	PAL
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.01Lux@ (F1.2 , AGC ON)
Lens	3.6mm@F1.8 angle of view : 70.6°
Lens Mount	M12
Day& Night	Electronic color to black
Compression Standard	
Video Compression	H.264
Bit Rate	32 Kbps~8Mbps
Audio Compression	OggVorbis
Image	
Max Image Resolution	704×576
Frame Rate	25fps (704×576)
Network	
Storage	Support SD/SDHC
Alarm Trigger	Motion detection
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (FTP,SMTP,NTP,SNMP)
Common functions	dual stream, heartbeat
Interface	
Audio Input	2 channel 3.5mm audio interface (2.0~2.4Vp-p, 1k Ohm)
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	2 channel
Alarm Output	2 channel
Video output	Test Monitor OUT 1Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%
Power Consumption	9W MAX
IR Range	10M
Dimensions	φ150×123
Weight	550g

Features

- High performance TI DSP chip
- H.264 Video Compression
- Day and night monitoring
- Support SD/SDHC card storage
- PTZ