



### Features

- 1.3 megapixel (1280 x 960) High Resolution
- 1/3" Progressive Scan CCD
- Micro SD/SDHC memory
- H.264/MPEG4 Video Compression
- PTZ、POE

Model	VD-C2130S
Image Sensor	1/3" CMOS
Signal system	PAL
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.01Lux@ ( F1.2 , AGC ON)
Shutter Time	1/4s~1/100,000s
Lens Mount	C/CS interface
Auto Iris Lens	DC drive
Day& Night	Electronic color to black
Compression Standard	
Video Compression	H.264/MPEG4
Bit Rate	32 Kbps~8Mbps
Audio Compression	OggVorbis
Image	
Max Image Resolution	1280×960
Frame Rate	50Hz:12.5fps ( 1280×960 ) , 25fps ( 1280×720 ) 60Hz:10fps ( 1280×960 ) , 24fps ( 1280×720 )
Network	
Storage	Support SD/SDHC
Alarm Trigger	Motion detection,
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE (FTP,SMTP,NTP,SNMP )
Common functions	dual stream, heartbeat, Password protection
Interface	
Audio Input	1 channel 3.5mm audio interface (2.0~2.4Vp-p, 1k Ohm)
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	1 channel
Alarm Output	2 channel
Video output	1Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE/AC24V±10%
Power Consumption	10W MAX
Dimensions	67.95×56×114.8
Weight	800g