

VD-C2130HS

1.3MP Network Box Camera



Model	VD-C2130HS
Image Sensor	1/3" CMOS
Signal system	PAL/NTSC
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.01Lux@ (F1.2 , AGC ON)
Shutter Time	1/25(1/30)s~1/100 , 000s
Lens Mount	C/CS interface
Auto Iris Lens	DC drive
Day& Night	ICR Cut Filter
Compression Standard	
Video Compression	H.264/MJPEG
Bit Rate	32 Kbps~16Mbps
Audio Compression	G.711
Image	
Max Image Resolution	1280×960
Frame Rate	50Hz:12.5fps (1280×960) , 25fps (1280×720) 60Hz:15fps (1280×960) , 30fps (1280×720)
Network	
Storage	Support SD/SDHC,NAS/ISCS
Alarm Trigger	Motion detection, Video loss , network disconnect, IP address conflict, storage full, storage error
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE , SMTP,NTP (SNMP,HTTPS,FTP,SIP,SRTSP,802.1×IPV6)
Common functions	One key reset, flicker, dual stream, heartbeat,
Interface	
Audio Input	1 channel microphone input, 3.5mm mini-jack
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	1 channel
Alarm Output	1channel
	1Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE/AC24V±10%
Power Consumption	12.5W MAX
Dimensions	68×57×114.8
Weight	500g

Features

- 1.3 megapixel (1280 x 960)
- High Resolution
- Full HD 720P real-time video
- 1/3" Progressive Scan CCD
- Support SD/SDHC card storage
- ICR Cut Filter Auto switch
- PoE