



Model	VD-C5130HS
Image Sensor	1/3" CMOS
Minimum Illumination	Color : 0.01lux@(F1.2,AGC ON);B/W : 0.001Lux@ (F1.2 , AGC ON)
Shutter Time	1/25s~1/100,000s
Lens	2.7-9mm@F1.2 angle of view : 101°-30.4°
Lens Mount	φ14
Auto Iris Lens	DC drive
Day& Night	ICR Cut Filter
Wide dynamic range	120dB
digital noise reduction	3D digital noise reduction
Compression Standard	
Video Compression	H.264/MPEG4/MJPEG
Bit Rate	32 Kbps~16Mbps
Audio Compression	G.711
Audio Bit rate	64kbps(G.711)
Image	
Max Image Resolution	1280×960
Frame Rate	50Hz:25fps (1280×960) , 25fps (1280×720) 60Hz:30fps (1280×960) , 30fps (1280×720)
Network	
Storage	Support SD/SDHC,NAS/ISCS
Alarm Trigger	Motion detection, tampering alarm , network disconnect, IP address conflict,storage full, storage error
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (SNMP,HTTPS,FTP,SIP,SRTP,802.1×IPV6)
Interface Protocols	ONVIF,PSIA,CGI
Common functions	flicker, dual stream, heartbeat,image , Video shade
Interface	
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE
Power Consumption	12W MAX
Protection grade	IP66
ICR Range	20-30M
Dimensions	98×88.6×328.8
Weight	1700g

Features

- 1.3 megapixel (1280 x 960) High Resolution
- H.264/MPEG4/MJPEG Video Compression
- IR LEDs Length 20-30M
- 1/3" Progressive Scan CCD
- IP66 Ingress Protection
- ICR Cut Filter Auto switch
- True day / night