



|                                 |   |
|---------------------------------|---|
| Model                           | VD-C2200T   |
| Image Sensor                    | 1/3" CCD  |
| Minimum Illumination            | Color : 0.5lux@(F1.2,AGC ON);0.1lux@(F1.2,AGC ON , iso×5)<br>B/W : 0.05Lux@ ( F1.2 , AGC ON);0.01lux@ ( F1.2 , AGC ON , iso×5)  |
| Shutter Time                    | 1/25s~1/100,000s  |
| Lens Mount                      | C/CS Interface  |
| Auto Iris Lens                  | DC drive  |
| Day& Night                      | Electronic color to black   |
| Compression Standard            |   |
| Video Compression               | H.264/MJPEG   |
| Bit Rate                        | 32 Kbps~16Mbps  |
| Audio Compression               | G.711   |
| Image                           |   |
| Max Image Resolution            | 1600×1200   |
| Frame Rate                      | 50Hz:12.5fps ( 1600×1200 ) , 12.5fps ( 1600×712 ) 25fps ( 1280×960 )<br>25fps ( 1280×720 ) 60Hz:15fps ( 1600×1200 ) , 15fps ( 1600×912 )<br>25fps ( 1280×960 ) , 30fps ( 1280×720 ) |
| Network                         |   |
| Storage                         | Support SD/SDHC,NAS/ISCS  |
| Alarm Trigger                   | Motion detection,Video loss , , network disconnect,<br>IP address conflict,storage full, storage error  |
| Protocols                       | TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP<br>(SNMP,HTTPS,FTP,SIP,SRTP,802.1×IPV6 )  |
| Common functions                | e-PTZ , One key reset, flicker, dual stream, heartbeat,   |
| Interface                       |   |
| Audio Input                     | 1 channel microphone input, 3.5mm mini-jack   |
| Audio Output                    | 1 channel 3.5mm audio interface (line level, 600 Ohm)   |
| Communication Interface         | 1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface  |
| Alarm Input                     | 1 channel   |
| Alarm Output                    | 1 channel   |
| Video output                    | 1Vp-p Composite Output(75Ω/BNC)   |
| General                         |   |
| Working TemperatureAnd humidity | -10°C~60°C , humidity 90% or less (non-condensing)  |
| Power Supply                    | DC12V±10%/POE/AC24V   |
| Power Consumption               | 9.5W MAX  |
| Dimensions                      | 68×57×144.8   |
| Weight                          | 550g  |

### Features

- 2 megapixel (1600×1200) High Resolution
- 1/3" Progressive Scan CCD
- Support SD/SDHC card storage
- ICR Cut Filter Auto switch
- True day / night
- PoE