



Model	VD-C2200WDS
Image Sensor	1/3" CMOS
Minimum Illumination	Color : 0.05lux@(F1.2,AGC ON) B/W : 0.005Lux@ ( F1.2 , AGC ON)
Shutter Time	1/25s~1/100,000s
Lens Mount	C/CS Interface
Auto Iris Lens	DC drive
Day& Night	ICR Cut Filter
digital noise reduction	3D digital noise reduction
Compression Standard	
Video Compression	H.264/MPEG4/MJPEG
Bit Rate	32 Kbps~16Mbps
Audio Compression	G.711
Audio Bit rate	64Kbps
Image	
Max Image Resolution	1920×1080
Frame Rate	50Hz:25fps ( 1920×1080 ) 60Hz:30fps ( 1920×1080 )
Network	
Storage	Support SD/SDHC,NAS/ISCS
Alarm Trigger	Motion detection,Occlusion alarm, IP address conflict,storage full, storage error
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (SNMP,HTTPS,FTP,SIP,SRTP,802.1×IPV6 )
Interface Protocols	ONVIF,PSIA,CGI
Common functions	One key reset, flicker, dual stream, heartbeat,
Interface	
Audio Input	1 channel microphone input, 3.5mm mini-jack
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	1 channel
Alarm Output	1 channel
Video output	1Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE/AC24V
Power Consumption	9.5W MAX
Dimensions	68×64.9×144.8
Weight	550g

## Features

- 2 megapixel (1600×1200) High Resolution
- Full HD 1080P real-time video
- 1/3" Progressive Scan CCD
- Support 32G SD/SDHC card storage
- ICR Cut Filter Auto switch
- True day / night
- PoE