



Model	VD-C5200HS
Image Sensor	1/3" CMOS
Minimum Illumination	Color : 0.01lux@(F1.2,AGC ON) B/W : 0.001Lux@ (F1.2 , AGC ON)
Shutter Time	1/25s~1/100,000s
lens	2.7-9mm @ F1.2 , angle of view : 101°-30.4°
Lens Mount	φ14
Auto Iris Lens	DC drive
Day& Night	ICR Cut Filter
Wide dynamic range	120dB
digital noise reduction	3D digital noise reduction
Compression Standard	
Video Compression	H.264/MPEG4/MJPEG
Bit Rate	32 Kbps~16Mbps
Audio Compression	G.711
Audio Bit rate	64Kbps (G.711)
Image	
Max Image Resolution	1920×1080
Frame Rate	50Hz:25fps (1920×1080) , 25fps (1280×960) 60Hz:30fps (1920×1080) , 30fps (1280×960)
Network	
Storage	Support NAS/iSCSI
Alarm Trigger	Motion detection, Occlusion alarm, IP address conflict, storage full, storage error
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPOE, SMTP, NTP (SNMP, HTTPS, FTP, SIP, SRTP, 802.1×IPV6)
Interface Protocols	ONVIF, PSIA, CGI
Common functions	flicker, dual stream, heartbeat, mirror image , Video occlusion
Interface	
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port
General	
Working Temperature And humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE
Power Consumption	12W MAX
Protection grade	IP66
ICR Range	20-30M
Dimensions	98×88.6×328.8
Weight	1700g

Features

- 2 megapixel (1920×1080) High Resolution
- IR LEDs Length 20-30M
- 120dB wide dynamic range
- 1/3" Progressive Scan CCD
- IP66 Ingress Protection
- PoE