

# VD-C2300HS

# 3MP Network Box Camera



Model	VD-C2300HS
Image Sensor	1/3" CMOS
Minimum Illumination	Color : 0.6lux@(F1.2,AGC ON) B/W : 0.08Lux@ ( F1.2 , AGC ON)
Shutter Time	1/25s~1/100,000s
Lens Mount	C/CS Interface
Auto Iris Lens	DC drive
Day& Night	ICR Cut Filter
Compression Standard	
Video Compression	H.264/MJPEG
Bit Rate	32 Kbps~16Mbps
Audio Compression	G.711
Image	
Max Image Resolution	2048×1536
Frame Rate	50Hz:12.5fps ( 2048×1536 ) , 25fps ( 1920×1080 ) , 25fps ( 1600×1200 ) , 60Hz:15fps ( 2048×1536 ) , 30fps ( 1920×1080 ) , 30fps ( 1600×1200 )
Network	
Storage	Support SD/SDHC,NAS/iSCSI
Alarm Trigger	Motion detection,Video loss , network disconnect, IP address conflict,storage full, storage error
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (SNMP,HTTPS,FTP,SIP,SRTP,802.1×IPV6 )
Common functions	One key reset, flicker, dual stream, heartbeat,
Interface	
Audio Input	1 channel microphone input, 3.5mm mini-jack
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	1 channel
Alarm Output	1 channel
Video output	1Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE/AC24V
Power Consumption	10.5W MAX
Dimensions	68×57×144.8
Weight	520g

## Features

- 3 megapixel (2048×1536) High Resolution
- Full HD 1080P real-time video
- H.264/MPEG4 Video Compression
- Support SD/SDHC card storage
- ICR Cut Filter Auto switch
- True day / night
- PoE