

# VD-C2500HS

# 5MP Network Box Camera



Model	VD-C2500HS
Image Sensor	1/2.5" CMOS
Minimum Illumination	Color : 0.6lux@(F1.2,AGC ON) B/W : 0.08Lux@ ( F1.2 , AGC ON)
Shutter Time	1/25s~1/200,000s
Lens Mount	C/CS mount
Auto Iris Lens	DC drive
Day& Night	ICR Cut Filter
Compression Standard	
Video Compression	H.264/MJPEG
Bit Rate	32 Kbps~16Mbps
Audio Compression	G.711
Image	
Max Image Resolution	2560×1920
Frame Rate	50Hz:8fps ( 2560×1920 ) , 20fps ( 2048×1536 ) , 25fp ( 1920×1080 ) 25fps ( 1280×720 ) 60Hz:8fps ( 2560×1920 ) 20fps ( 2048×1536 ) , 30fps ( 1920×1080 ) 30fps ( 1280×720)
Network	
Storage	Support SD/SDHC,NAS/ISCS
Alarm Trigger	Motion detection,Occlusion alarm,Video loss , network disconnect, IP address conflict,storage full, storage error
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE,SMTP,NTP (SNMP,HTTPS,FTP,SIP,SRTP,802.1×IPV6 )
Common functions	One key reset, flicker, dual stream, heartbeat,
Interface	
Audio Input	1 channel 3.5mm audio interface (2.0~2.4Vp-p, 1k Ohm)
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	4 channel
Alarm Output	3 channel
Video output	1Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C , humidity 90% or less (non-condensing)
Power Supply	DC12V±10%/POE/AC24V
Power Consumption	13W MAX
Dimensions	68×77×164
Weight	11000g

## Features

- 5 megapixel 8fps@(2048×1536)
- High Resolution
- Full HD 1080P real-time video
- H.264/MPEG4 Video
- Compression
- Support SD/SDHC card storage
- ICR Cut Filter Auto switch
- True day / night
- PoE