



| | |
|---------------------------------|--|
| Model | VD-C5054HS |
| Image Sensor | 1/3" CMOS |
| Signal system | PAL/NTSC |
| Minimum Illumination | Color : 0.1lux@(F1.2,AGC ON);B/W : 0.001Lux@ (F1.2 , AGC ON) |
| Shutter Time | 1/50(1/60)s~1/100,000s |
| Lens Mount | M12 |
| Auto Iris Lens | 3.6MM/6MM/8MM/12MM/16MM |
| Day& Night | Electronic color to black |
| Wide dynamic range | 540 TVL |
| Compression Standard | |
| Video Compression | H.264/MJPEG |
| Bit Rate | 32 Kbps~8Mbps |
| Audio Compression | OggVorbis |
| Image | |
| Max Image Resolution | PAL:704×576 NTSC:704×480 |
| Frame Rate | 50Hz:25fps (704×576) 60Hz:30fps (704×480) |
| Network | |
| Alarm Trigger | Motion detection |
| Protocols | TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE, (FTP,SMTP,NTP,SNMP) |
| Common functions | dual stream, heartbeat, |
| Interface | |
| Audio Input | 1 channel 3.5mm audio interface (2.0~2.4Vp-p, 1k Ohm) |
| Audio Output | 1 channel 3.5mm audio interface (line level, 600 Ohm) |
| Communication Interface | 1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface |
| Alarm Input | 1 channel |
| Alarm Output | 1 channel |
| Video output | 1Vp-p Composite Output(75Ω/BNC) |
| General | |
| Working TemperatureAnd humidity | -10°C~60°C |
| Power Supply | DC12V±10% |
| Power Consumption | 9W MAX |
| Protection grade | IP66 |
| ICR Range | 10-20m ; 30-40m ; 50-60m |
| Dimensions | 87×83×228 |
| Weight | 1400g |

Features

- H.264/MJPEG Video Compression
- IP66 Ingress Protection
- PTZ