



Model	VD-C5054HT
Image Sensor	1/3" CCD
Signal system	PAL/NTSC
Minimum Illumination	Color : 0.1lux@(F1.2,AGC ON);B/W : 0.001Lux@ (F1.2 , AGC ON)
Shutter Time	1/50(1/60)s~1/100,000s
Lens Mount	M12
Auto Iris Lens	3.6MM/6MM/8MM/12MM/16MM
Day& Night	Electronic color to black
Wide dynamic range	540 TVL
Compression Standard	
Video Compression	H.264/MJPEG
Bit Rate	32 Kbps~8Mbps
Audio Compression	OggVorbis
Image	
Max Image Resolution	PAL:704×576 NTSC:704×480
Frame Rate	50Hz:25fps (704×576) 60Hz:30fps (704×480)
Network	
Alarm Trigger	Motion detection
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE, (FTP,SMTP,NTP,SNMP)
Common functions	dual stream, heartbeat,
Interface	
Audio Input	1 channel 3.5mm audio interface (2.0~2.4Vp-p, 1k Ohm)
Audio Output	1 channel 3.5mm audio interface (line level, 600 Ohm)
Communication Interface	1 RJ45 10M/100M self adaptive Ethernet port and 1 RS-485 interface
Alarm Input	1 channel
Alarm Output	1 channel
Video output	1Vp-p Composite Output(75Ω/BNC)
General	
Working TemperatureAnd humidity	-10°C~60°C
Power Supply	DC12V±10%
Power Consumption	9W MAX
Protection grade	IP66
ICR Range	10-20m ; 30-40m ; 50-60m
Dimensions	87×83×228
Weight	1400g

Features

- H.264/MJPEG Video Compression
- IP66 Ingress Protection
- PTZ